



# **SENTINO** EASY 2 WASH

**Luxury Acrylic Emulsion for Interior** 

### **PRODUCT DESCRIPTION**

SENTINO EASY 2 WASH is a Luxury Interior Emulsion which gives rich sheen finish with superior washability of stubborn stains on your wall surfaces. It is formulated with a special cross linking polymers which keeping the paint film intact for a longer period of time. Used superior pigments and very selective grades of extenders and silicon additives with the various functionalities to enhance the product performance. It gives smooth & sheen finish and fresh look for years at an affordable price.

### **SURFACE PREPARATION**

#### **PLASTER**

New masonry surfaces must be allowed to cure completely. Recommended curing time is 28 days minimum. A base coat of SNOWCARE SEALER & PRIMER for better finish before application of **SENTINO EASY 2 WASH** can also be done.



### **CLEANING**

Surface must be clean and sound, free from all dust, oil, grease and other contaminations. Remove all loose material with scrapper or stiff wire brush. Dampness of the wall has to be treated with appropriate measures.



### FILLING THE CRACKS, HOLES & DENTS

For filling cracks upto 3mm, holes and dents use Snowcare Wall Putty or white cement and fine sand in the ratio 1:3 For interior surfaces or substrates that are subjected to continuous seepage or dampness, kindly get the repairs done before the application.



### **PAINT APPLICATION PROCESS**

SNOWCARE SEALER PRIMER Brush/Roller/Spray

SNOWCARE WALL PUTTY OR SNOWCEM ACRYLIC PUTTY Trowel

SNOWCARE SEALER PRIMER Brush/Roller/Spray

SENTINO EASY 2 WASH Brush/Roller/Spray

SENTINO EASY 2 WASH Brush/Roller/Spray

### DILUTION

500ml of water to 1litre of paint

40% dilution with water No dilution

500ml of water to 1litre of paint

400ml of

water to 1litre of paint

400ml of water to 1litre of paint

4 - 6 hrs

RECOATING PERIOD

4 hrs

ON

4 hrs

4 - 6 hrs

4 - 6 hrs

Recoat period is quoted for 25°C and 50% Relative Humidity; these may vary under different conditions. Some shades may require 3 coats for proper hiding.

HORIZONTAL SURFACES LIKE TOP OF WINDOWS, LEDGES SHOULD BE PAINTED WITH 3 COATS OF SENTINO EASY  ${f 2}$  WASH FOR GREATER PROTECTION APPLICATION OF SUITABLE PRIMER IS MUST.

**Special note on cleaning:** Before cleaning let the paint film form properly for minimum 15 days. To clean the stains, apply mild liquid soap solution (turpentine can be used for oil based stains) and wipe clean.

### **Cleaning Instructions:**

- Use only a mild soap to clean stains
- To Clean oil based stains use mineral turpentine oil only
- Use only a soft white cotton cloth for cleaning
- While cleaning, wipe gently without using pressure
- Attempt cleaning the surface only after two weeks of application

### **PRODUCT FEATURES**

High Washability & Scrub Resistance

Elegant Appearance with Soft Sheen

High Durability with **Non-Stick Flim** 

Strong adhesion properties

Excellent flow & levelling

Fungi-Algae Resistant

6 Years Performance Warranty

### **COLOURS AVAILABLE**

1500+\*\* Currently available in more than 1500 shades as per the Snowcem Paints Colour Spectra



### **MIXING RATIO**

Dilute one liter of **SENTINO** EASY 2 WASH with 400 ml of clean potable water. Do not add any stainer/colorant to the SENTINO EASY 2 WASH. Don't over dilute SENTINO EASY 2 WASH.



### **COVERAGE:**

Varies according to the porosity and texture of the surface. Coverage for smooth surface with no suction: On normal masonry surface coverage would be 240-280 sq.ft. per litre per coat.



### **AVAILABLE PACK SIZES**

The pack sizes available for **SENTINO EASY 2 WASH** are 4t and 1t only.





# SENTINO EASY 2 WASH

**Luxury Acrylic Emulsion for Interior** 

## TECHNICAL DETAILS

Nature	Thixotropic
Base	Pure Acrylic emulsion
Finish	Smooth pleasant finish
Mode of application	By brush, roller or spray
Drying time	20-30 min for touch dry (65% relative humidity/30°C.)
Recoating Period	4 to 6 hours.
Flash Point	N. A. as it is water based paints
Gloss Level	8 - 15 at 60°GH / 40 - 60 at 85°GH

## HANDLING & STORAGE

Keep containers airtight during handling and storage to avoid loss of material. Store **SENTINO EASY 2 WASH** in a cool dry place and also protect it from extreme climatic conditions during storage, in transit and at site.

### SAFETY MEASURES

Kindly refer to the MSDS for Snowcem Paints **SENTINO EASY 2 WASH** which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion seek immediate medical attention. In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

In the event of spills, contain spillage using sand or earth.

### POST PAINTING CARE

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

### Corporate office:

3rd Floor, Agrima Business Centre, N. K. Mehta International House, 178, Backbay Reclamation, Babubhai Chinai Marg, Mumbai - 400 020. Maharashtra, India.

### Branches

Ahmedabad | Bangalore | Ghaziabad | Jaipur | Kochi | Kolkata | Mumbai | New Delhi | Pune | Secunderabad CFA Locations:

Cuttack | Indore | Jamshedpur | Kanpur | Nagpur | Raipur | Salem | Visakhapatnam

Eco-friendly Commitment: All products of Snowcem Paints are Lead, Chromium and Mercury free Please consider the environment before printing it.

## GREEN BUILDING PARAMETERS

SENTINO EASY 2 WASH qualifies for "GREEN BUILDING CRITERIA"

### REFERENCE

Type of Paint

Exterior Flat

**LEEDS\***100 g/t VOC
50 g/t VOC

**TERI GRIHA**\*
100 g/t VOC
50 g/t VOC

As per IS 15489 : 2004, Section 6.12.2.1 specifies the "product not to contain more than 5%, by mass, Volatile Organic Compounds"

\* LEED - Leadership in Environment and Energy Design, USA. # TERI - The Energy and Resource Institute, India. GRIHA - Green Rating Integrated Habitat Assessment.

## VOLATILE ORGANIC COMPOUNDS

SENTINO EASY 2 WASH contains less than 40 g/t VOC. SENTINO EASY 2 WASH contains 1-3% VOC.



### **HEAVY METALS**

**SENTINO EASY 2 WASH** is free from lead, chromium (VI), cadmium, mercury and its compounds.



### HAZARDOUS CHEMICALS

sentino EASY 2 WASH does not contain harmful compound like formaldehyde, phenolic compounds, benzene, etc.



